# Statement of Basis Automotive Coating Operations General Permit

**Proposed for Public Comment/Final** 

Permittee Facility Name City, Idaho Facility ID No. XXX-XXXXX Permit to Construct P-2010.xxxx Project No. 00000

> Date Name Permit Writer

The purpose of this Statement of Basis is to satisfy the requirements of IDAPA 58.01.01.et seq, Rules for the Control of Air Pollution in Idaho, for issuing air permits.

ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE	
FACILITY INFORMATION	4
Description	4
Permitting History	4
Application Scope	4
Application Chronology	4
TECHNICAL ANALYSIS	5
Emissions Units and Control Devices	5
Emissions Inventories	5
Ambient Air Quality Impact Analyses	8
REGULATORY ANALYSIS	9
Attainment Designation (40 CFR 81.313)	9
Facility Classification AIRS/AFS	9
PTC Permit to Construct (IDAPA 58.01.01.201)	
Tier II Operating Permit (IDAPA 58.01.01.401)	
Visible Emissions (IDAPA 58.01.01.625)	
Rules for the Control of Odors (IDAPA 58.01.01.775-776)	
Title V Classification (IDAPA 58.01.01.300, 40 CFR Part 70)	
PSD Classification (40 CFR 52.21)	
NSPS Applicability (40 CFR 60)	
NESHAP Applicability (40 CFR 61)	
MACT Applicability (40 CFR 63)	
Permit Conditions Review	
PUBLIC REVIEW	
Public Comment Opportunity	17
Public Comment Period	
APPENDIX A – EMISSIONS INVENTORIES	

# ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE

AQCR	Air Quality Control Region
Btu	British thermal units
CAS No.	Chemical Abstracts Service registry number
CE	Control Efficiency
CFR	Code of Federal Regulations
CO	carbon monoxide
DEQ	Department of Environmental Quality
EL	screening emission levels
EPA	U.S. Environmental Protection Agency
gal/day	gallons per calendar day
gal/hr	gallons per hour
gal/yr	gallons per consecutive 12 calendar month period
gr	grain $(1 \text{ lb} = 7,000 \text{ grains})$
HAP	hazardous air pollutants
hr/yr	hours per year
HVLP	high volume, low pressure (applies to paint guns)
IDAPA	a numbering designation for all administrative rules in Idaho promulgated in accordance with the
	Idaho Administrative Procedures Act
lb/gal	pounds per gallon
lb/hr	pounds per hour
LPG	Liquefied Petroleum Gas
MMBtu	million British thermal units
MSDS	Material Safety Data Sheet
NAICS	North American Industry Classification System
NESHAP	National Emission Standards for Hazardous Air Pollutants
$NO_2$	nitrogen dioxide
$NO_X$	nitrogen oxides
NSPS	New Source Performance Standards
PC	permit condition
$PM_{10}$	particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers
ppm	parts per million
PTC	permit to construct
PTE	potential to emit
Rules	Rules for the Control of Air Pollution in Idaho
scf	standard cubic feet
SIC	Standard Industrial Classification
SM80	synthetic minor facility with emissions greater than or equal to 80% of a major source threshold
$SO_2$	sulfur dioxide
SO <sub>X</sub>	sulfur oxides
T/yr	tons per consecutive 12-calendar month period
T2	Tier II operating permit
TAP	toxic air pollutants
TE	Transfer Efficiency
UTM	Universal Transverse Mercator
VOC	volatile organic compounds

# FACILITY INFORMATION

# Description

Note: This template evaluation is to be used for Automotive Coatings operations that agree to use 4.0 gal/day or less for all coating materials and do not propose to use MeCl for paint-stripping activities. If the application does not meet these requirements it cannot be processed as a "General Permit" with this template evaluation. In addition, as of January 11, 2011 all facilities will be considered "new" for Subpart 6H.

During processing all notes in dark red and hints in *red italics* are to be deleted. Items in blue are to be edited by the processing engineer. Remember to do a search for "xx" to see if there is anything that was missed during processing.

*[Note: Modify the following paragraph as applicable.]* Business Name is an auto body repair and refinishing facility with paint spray booth(s) which is/are equipped with a paint booth heater. The paint booth(s) is a pressurized downdraft/semi-downdraft/side draft booth(s) with glass fiber filtration media *[or]* a water wall system for control of particulate emissions. Drying and paint curing is done in the paint booth(s). The booth(s) is/are equipped with a natural gas-fired *[or]* LPG burner to heat the paint booth. The process includes application of coatings via a HVLP (or equivalent) paint gun.

# **Permitting History**

This is the initial PTC for a new facility thus there is no permitting history.

*{or}* 

This is the initial PTC for an existing facility that was constructed in Month, Year thus there is no permitting history.

### {*or*}

The following information was derived from a review of the permit files available to DEQ. Permit status is noted as active and in effect (A) or superseded (S).

Date Field P-2010.xxxx, Permitting action description, Permit status (A) or (S)

# **Application Scope**

*(Modify the following paragraph for PTC projects.)* This is the initial PTC for a new facility. *(or)* This is the initial PTC for an existing facility that was constructed in Month, Year.

# Application Chronology

Month Day, Year	DEQ sent a notice of violation to the facility, which included notification that a PTC was required (Enforcement Case No. E-XXXXXX).
Month Day, Year	DEQ received an application and an application fee and the processing fee.
Month Day – Month Day, Year	DEQ provided an opportunity to request a public comment period on the application and proposed permitting action.
Month Day, Year	{For 15-day approval projects} DEQ approved pre-permit construction.
Month Day, Year	DEQ determined that the application was incomplete.
Month Day, Year	DEQ received supplemental information from the applicant.
Month Day, Year	DEQ determined that the application was complete.
Month Day, Year	DEQ made available the draft permit and statement of basis for peer review.

Month Day – Month Day, Year DEQ provided a public comment period on the proposed action.

Month Day, Year	DEQ received the permit processing fee. { <i>Note: Remove if all of the fees were paid up front.</i> }
Month Day, Year	DEQ issued the final permit and statement of basis.

# **TECHNICAL ANALYSIS**

*(Note: Modify the following paragraph as applicable.)* The facility utilizes glass fiber filtration media *(or)* a water wall system for control of particulate matter emissions from the automotive coating operation. In addition, HVLP paint guns (or equivalent) are used to minimize  $PM_{10}$  and VOC emissions from painting. The HVLP (or equivalent) spray equipment will control  $PM_{10}$  and VOC emissions by having more paint transfer to the desired surfaces than traditional painting equipment.

# **Emissions Units and Control Devices**

# {Note: Add additional rows if there is more than one paint booth at the facility.}

#### **Emissions Point** ID No. **Source Description Control Equipment Description** ID No. and Description Paint spray booth(s) and/or preparation station filter system: Booth Type(s): Down draft/Semi-down draft/Side draft Particulate filtration method: Dry Filters/Wet Wall Paint spray booth(s) and/or preparation station: Manufacturer(s): XXX or equivalent Manufacturer(s): XXX or equivalent Model(s): XXX or equivalent PM/PM<sub>10</sub> Control Efficiency: XX.XX% or greater Model(s): XXX or equivalent Note: The number of booths installed at the *{Note: HHHHHH requires 98% control and emissions* facility is not limited by this permit. are based upon 98% control. Even if the Applicant Paint booth specifies a higher control efficiency, leave this at 98% exhaust stack Automotive {If installed} Paint booth heater(s): since that is what the permit conditions specify.} and/or Coating Manufacturer(s): XXX or equivalent preparation Operation Model(s): XXX or equivalent station exhaust Coating spray gun(s): Total Heat input capacity(s): X.XXX MMBtu/hr Manufacturer(s): XXX or equivalent stack (worst-case was assumed to be 2.0 MMBtu/hr) Model(s): XXX or equivalent *Note: Use 2.0 MMBtu for natural gas burners* Type: HVLP or equivalent and 1.2 MMBtu/hr for LPG burners.} Transfer Efficiency: 65% or greater Fuel: natural gas only *(or)* LPG only *Note: HHHHHH requires a 65% transfer efficiency* and emissions are based upon a 65% transfer efficiency. Even if the Applicant specifies a higher transfer efficiency, leave this at 65% since that is what the permit conditions specify.}

# Table 1 EMISSIONS UNIT AND CONTROL DEVICE INFORMATION

# **Emissions Inventories**

# Potential to Emit

IDAPA 58.01.01.006 defines Potential to Emit as the maximum capacity of a facility or stationary source to emit an air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the facility or source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is state or federally enforceable. Secondary emissions do not count in determining the potential to emit of a facility or stationary source.

Using this definition of Potential to Emit an emission inventory was developed for the automotive coating operation associated with this proposed project (see Appendix A for detailed potential to emit calculations). Criteria pollutant and HAPs PTE were based on the worst-case VOC,  $PM_{10}$ , and HAPs content for coatings as taken from the DEQ Automotive Coating EI spreadsheet (see the DEQ website).

## **Uncontrolled Potential to Emit**

Using the definition of Potential to Emit, uncontrolled Potential to Emit is then defined as the maximum capacity of a facility or stationary source to emit an air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of the facility or source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored or processed, shall <u>not</u> be treated as part of its design <u>since</u> the limitation or the effect it would have on emissions <u>is not</u> state or federally enforceable.

The uncontrolled Potential to Emit is used to determine if a facility is a "Synthetic Minor" source of emissions. Synthetic Minor sources are facilities that have an uncontrolled Potential to Emit for criteria pollutants or HAPs above the applicable Major Source threshold without permit limits.

The following table presents the uncontrolled Potential to Emit for criteria pollutants as determined by DEQ staff. See Appendix A for a detailed presentation of the calculations and the assumptions used to determine emissions for each emissions unit. For this automotive coating operation uncontrolled Potential to Emit is based upon a worst-case for operation of the facility of 2,080 hrs/yr (8 hrs/day x 260 days/yr) with all coating operations occurring during this time. Since there is prep time (the time spent preparing the automobile for the application of coating) and paint drying time (the time the automobile spends in the booth with the burner operating to facilitate hardening of the coating) associated with applying coatings, this was considered to be the worst-case maximum for which emissions would occur.

# {*The following table is automated. Selecting the "Total, Point Sources" row and pressing the F9 key will automatically calculate/update the values of "Total, Point Sources".*}

Emissions Unit	PM <sub>10</sub> /PM <sub>2.5</sub>	$SO_2$	NO <sub>X</sub>	CO	VOC	Lead		
	T/yr	T/yr	T/yr	T/yr	T/yr	lb/quarter		
Point Sources								
Paint spray booth(s) and/or preparation station(s)	4.50	0.0	0.0	0.0	12.20	0.0		
<pre>Paint booth heater(s) {if installed}</pre>	0.016	0.001	0.196	0.083	0.011	0.0000020		
Total, Point Sources	4.52	0.00	0.20	0.08	12.21	0.00		

Table 2 UNCONTROLLED POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS

The following table presents the uncontrolled Potential to Emit for HAP pollutants as determined by DEQ staff. For this automotive coating operation uncontrolled HAP emissions were calculated by using the DEQ Automotive Coating EI spreadsheet (see the DEQ website) and setting paint use to 4.0 gallons per day (as limited by the permit). Then, the worst-case maximum HAPs Potential to Emit was determined for all paints listed in the spreadsheet. As discussed previously, HAP emissions were assumed to occur during the worst-case for operation of the facility of 2,080 hrs/yr.

HAP Pollutants	PTE (T/yr)
Ethyl benzene	0.61
Methyl Isobutyl Ketone (MIBK)	1.25
Naphthalene	2.32
Toluene	1.90
Styrene	2.49
Xylene (o-, m-, p-isomers)	2.20
Total	10.77

#### Table 3 UNCONTROLLED POTENTIAL TO EMIT FOR HAPs

#### **Pre-Project Potential to Emit**

Pre-project Potential to Emit is used to establish the change in emissions at a facility as a result of this project.

{Note: Use one of the following paragraphs as applicable.}

This is an existing facility. However, since this is the first time the facility is receiving a permit, pre-project emissions are set to zero for all criteria pollutants.

#### *{or}*

This is a new facility. Therefore, pre-project emissions are set to zero for all criteria pollutants.

#### Post Project Potential to Emit

Post project Potential to Emit is used to establish the change in emissions at a facility and to determine the facility's classification as a result of this project. Post project Potential to Emit includes all permit limits resulting from this project.

*Explain if this is for all emissions units at the facility (i.e. for new facilities) or for just the units being modified as a result of this project.* The following table presents the post project Potential to Emit for criteria pollutants from all emissions units at the facility as determined by DEQ staff. See Appendix A for a detailed presentation of the calculations of these emissions for each emissions unit.

# {*The following table is automated. Selecting the "Post Project Totals" row and pressing the F9 key will automatically calculate/update the values of "Post Project Totals".*}

Emissions Unit	PM <sub>10</sub> /	PM <sub>2.5</sub>	SC	$\mathbf{D}_2$	N	D <sub>X</sub>	С	0	VOC Lead		ad	
Emissions Unit	lb/hr <sup>a</sup>	T/yr <sup>b</sup>	lb/hr	T/yr								
					Point	Sources						
Paint spray booth(s) and/or preparation station(s)	0.02	0.09	0.00	0.00	0.00	0.00	0.00	0.00	2.79	12.20	0	0
Paint booth heater(s) {If installed}	0.0152	0.016	0.0012	0.001	0.188	0.196	0.080	0.083	0.011	0.011	0.0000010	0.0000010
Post-Project Totals	0.04	0.11	0.00	0.00	0.19	0.20	0.08	0.08	2.80	12.21	0.00	0.00

Table 4 POST PROJECT POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS

a) Controlled average emission rate in pounds per hour is a daily average, based on the proposed daily operating schedule and daily limits.

b) Controlled average emission rate in tons per year is an annual average, based on the proposed annual operating schedule and annual limits.

The following table presents the post project Potential to Emit for HAP pollutants from all emissions units at the facility as determined by DEQ staff. The DEQ Automotive Coating EI spreadsheet (see the DEQ website) was used to determine post project Potential to Emit for HAP pollutants.

HAP Pollutants	PTE (T/yr)
Ethyl benzene	0.61
Methyl Isobutyl Ketone (MIBK)	1.25
Naphthalene	2.32
Toluene	1.90
Styrene	2.49
Xylene (o-, m-, p-isomers)	2.20
Total	10.77

Table 5 POST PROJECT POTENTIAL TO EMIT FOR HAPs

### **Change in Potential to Emit**

The project's change in Potential to Emit is used to determine if a public comment period may be required or if emissions modeling may be required, and to determine the processing fee per IDAPA 58.01.01.225.

The following table presents the change in the Potential to Emit for criteria pollutants as a result of this project.

{*The following table is automated. Selecting the "Changes in Potential to Emit" row and pressing the F9 key will automatically calculate/update the values of "Changes in Potential to Emit".*}

	PM <sub>10</sub> /	'PM <sub>2.5</sub>	S	$O_2$	D <sub>2</sub> NO <sub>X</sub>		CO		VOC		Lead	
	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr	lb/hr	T/yr
					Point Sou	irces						
Pre-Project Potential to Emit	0.0	0.0	0.0.	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Post Project Potential to Emit	0.04	0.11	0.00	0.00	0.19	0.20	0.08	0.08	2.80	12.21	0.00	0.00
Changes in Potential to Emit	0.04	0.11	0.00	0.00	0.19	0.20	0.08	0.08	2.80	12.21	0.00	0.00

Table 6 CHANGES IN POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS

Non-Carcinogenic and Carcinogenic TAPs Potential to Emit

Because of the daily coating material use limits imposed by DEQ, and agreed to by the facility in applying for this Automotive Coating "General Permit", no ELs specified in IDAPA 58.01.01.585 or 586 are expected to be exceeded by the facility (see Appendix A).

# Ambient Air Quality Impact Analyses

Because of the daily coating material use limits imposed by DEQ, and agreed to by the facility in applying for this Automotive Coating "General Permit", it needs to be determined if the PTE for the automotive coating operation exceeds the DEQ modeling guideline thresholds. The following table compares the post-project facility-wide annual emissions to the DEQ modeling guideline thresholds (per the State of Idaho Air Quality Modeling Guideline, 12/31/2002).

Pollutant	PTE (T/yr) or lb/hr if listed	DEQ Modeling Guideline Thresholds (T/yr) or lb/hr if listed	Exceeds Modeling Guideline Threshold?
$PM_{10}$	0.11 and 0.04	1 and 0.2 lb/hr	No
PM <sub>2.5</sub>	0.11 and 0.04	0.35 and 0.054 lb/hr	No
$SO_2$	0.00 and 0.00	1 and 0.2 lb/hr	No
NO <sub>X</sub>	0.19 and 0.2	1 and 0.2 lb/hr	No
СО	0.08 lb/hr	14 lb/hr	No
Lead	0.00	14 lb/month	No

#### Table 7 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE DEQ MODELING GUIDELINE THRESHOLDS

Therefore, the installation of the new automotive coating operation does not require criteria pollutant modeling.

As presented previously in the DEQ Automotive Coatings EI Spreadsheet (see the DEQ website) there are no TAPs that required facility modeling for exceeding the pounds per hour screening levels provided in IDAPA 58.01.01.585 and .586. Therefore, the installation of a new automotive coating operation does not require TAPs modeling.

# **REGULATORY ANALYSIS**

## Attainment Designation (40 CFR 81.313)

*(attainment)* Facility name is located in XXX County, which is designated as attainment or unclassifiable for  $PM_{2.5}$ ,  $PM_{10}$ ,  $SO_2$ ,  $NO_2$ , CO, and Ozone. Refer to 40 CFR 81.313 for additional information.

*(non-attainment)* Facility name is located in XXX County, which is designated as attainment or unclassifiable for  $PM_{2.5}$ ,  $SO_2$ ,  $NO_2$ , CO, and Ozone, and non-attainment for  $PM_{10}$ . Refer to 40 CFR 81.313 for additional information.

# Facility Classification AIRS/AFS

"Synthetic Minor" for AIRS/AFS classification for criteria pollutants is defined as the uncontrolled Potential to Emit for criteria pollutants are above the applicable major source thresholds and the Potential to Emit for criteria pollutants fall below the applicable major source thresholds. Therefore, the following table compares the uncontrolled Potential to Emit and the Potential to Emit for criteria pollutants to the Major Source thresholds to determine if the facility will be "Synthetic Minor."

Table 8 UNCONTROLLED PTE AND PTE FOR CRITERIA POLLUTANTS COMPARED TO THE MAJOR SOURCE
THRESHOLDS

Pollutant	Uncontrolled PTE (T/yr)	PTE (T/yr)	Major Source Thresholds (T/yr)	Uncontrolled PTE Exceeds the Major Source Threshold and PTE Exceeds the Major Source Threshold?
$PM_{10}$	4.52	0.11	100	No
PM <sub>2.5</sub>	4.52	0.11	100	No
SO <sub>2</sub>	0.00	0.00	100	No
NO <sub>X</sub>	0.20	0.20	100	No
СО	0.08	0.08	100	No
VOC	12.21	12.21	100	No

"Synthetic Minor" for AIRS/AFS classification for HAP pollutants is defined as the uncontrolled Potential to Emit for HAP pollutants are above the applicable major source thresholds and the Potential to Emit for HAPs pollutants fall below the applicable major source thresholds. Therefore, the following table compares the uncontrolled Potential to Emit and the Potential to Emit for HAP pollutants to the Major Source thresholds to determine if the facility will be "Synthetic Minor."

HAP Pollutant	Uncontrolled PTE (T/yr)	PTE (T/yr)	Major Source Thresholds (T/yr)	Uncontrolled PTE Exceeds the Major Source Threshold and PTE Exceeds the Major Source Threshold?
Ethyl benzene	0.61	0.61	10	No
Methyl Isobutyl Ketone (MIBK)	1.25	1.25	10	No
Naphthalene	2.32	2.32	10	No
Toluene	1.90	1.90	10	No
Styrene	2.49	2.49	10	No
Xylene (o-, m-, p- isomers)	2.20	2.20	10	No
Total	10.77	10.77	25	No

Table 9 UNCONTROLED PTE AND PTE FOR HAPS POLLUTANTS COMPARED TO THE MAJOR SOURCE THRESHOLDS

As demonstrated in Table 8 the facility has an uncontrolled potential to emit for  $PM_{10}$ ,  $SO_2$ ,  $NO_x$ , CO, and VOC emissions are less than the Major Source thresholds of 100 T/yr for each pollutant. In addition, as demonstrated in Table 9 the facility has an uncontrolled potential for each HAP less than the Major Source threshold of 10 T/yr and for all HAPs combined less than the Major Source threshold of 25 T/yr. Therefore, this facility is not designated as a Synthetic Minor facility.

# PTC Permit to Construct (IDAPA 58.01.01.201)

IDAPA 58.01.01.201 Permit to Construct Required

The PTC rules under IDAPA 58.01.01.201 require that "No owner or operator may commence construction or modification of any stationary source, facility, major facility, or major modification without first obtaining a permit to construct from the Department which satisfies the requirements of Sections 200 through 228 unless the source is exempted in any of Sections 220 through 223." Therefore, DEQ staff analyzed the data from the permit application for the installation of this automotive coating operation to determine if it is exempt from obtaining a PTC according to Sections 220 through 223.

IDAPA 58.01.01.220 General Exemption Criteria for Permit to Construct Exemptions

In accordance with IDAPA 58.01.01.220.01.a, the maximum capacity of the source to emit an air pollutant under its physical and operational design without consideration of limitations on emissions such as air pollution control equipment, restrictions on hours of operation and restrictions on the type and amount of material combusted, stored, or processed shall not equal or exceed 100 tons/yr for all regulated air pollutants. As previously presented in Table 2, the proposed project results in uncontrolled potential emissions of less than 100 tons/yr for all regulated air pollutants. Therefore, the project meets the criteria set forth in Section 220 and may be exempt from PTC requirements. In addition, the criteria set forth in Section 221, 222, or 223 must be met to be exempt from PTC requirements.

#### IDAPA 58.01.01.221

Category I Exemption Criteria

In accordance with IDAPA 58.01.01.221.01, the maximum capacity of a source to emit an air pollutant under its physical and operational design considering limitations on emissions such as air pollution control equipment, restrictions on hours of operation and restrictions on the type and amount of material combusted, stored or processed shall be less than ten percent (10%) of the significant emission rates set out in the definition of significant at Section 006. The following table compares the post-project facility-wide annual PTE to 10% of the significance threshold listed in IDAPA 58.01.01.006.104 in order to determine if the project may qualify for a Category I exemption.

Pollutant	PTE (T/yr)	10% of the Significance Threshold (T/yr)	Exceeds 10% of the Significance Threshold?
$PM_{10}$	0.11	1.5	No
PM <sub>2.5</sub>	0.11	1.0	No
SO <sub>2</sub>	0.00	4.0	No
NO <sub>X</sub>	0.20	4.0	No
СО	0.08	10.0	No
VOC	12.21	4.0	Yes

Table 10 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE SIGNIFICANCE THRESHOLDS

The potential VOC emission rate of the proposed project is indicated in Table 10 above, which is above 10% of the significant emission rate listed in IDAPA 58.01.01.006.104. Therefore, the installation of a new/permitting of an existing automotive coating operation does not qualify for a Category I exemption.

# Tier II Operating Permit (IDAPA 58.01.01.401)

IDAPA 58.01.01.401 Tier II Operating Permit

The application was submitted for a permit to construct (refer to the Permit to Construct section), and an optional Tier II operating permit has not been requested. Therefore, the procedures of IDAPA 58.01.01.400–410 were not applicable to this permitting action.

# Visible Emissions (IDAPA 58.01.01.625)

IDAPA 58.01.01.625 Visible Emissions

The emissions from the automotive coating process are subject to the State of Idaho visible emissions standard of 20% opacity. This requirement is assured by Permit Condition 6.

# Rules for the Control of Odors (IDAPA 58.01.01.775-776)

IDAPA 58.01.01.775-776 Rules for the Control of Odors

The facility is subject to the general restrictions for the control of odors from the facility. This requirement is assured by Permit Conditions 7 and 12.

# Title V Classification (IDAPA 58.01.01.300, 40 CFR Part 70)

IDAPA 58.01.01.301 Requirement to Obtain Tier I Operating Permit

IDAPA 58.01.01.006 defines a Tier I source as "Any source located at a major facility as defined in Section 008." IDAPA 58.01.01.008 defines a Major Facility as either:

• For HAPS a facility with the potential to emit ten (10) tons per year (T/yr) or more of any hazardous air pollutant, other than radionuclides, or

• The facility emits or has the potential to emit twenty-five (25) T/yr or more of any combination of any hazardous air pollutants, other than radionuclides.

Or, for non-attainment areas:

- The facility is located in a "serious" particulate matter ( $PM_{10}$ ) nonattainment area and the facility has the potential to emit seventy (70) T/yr or more of  $PM_{10}$ , or
- The facility is located in a "serious" carbon monoxide nonattainment area in which stationary sources are significant contributors to carbon monoxide levels and the facility has the potential to emit fifty (50) T/yr or more of carbon monoxide, or
- The facility is located in an ozone transport region established pursuant to 42 U.S.C. Section 7511c and the facility has the potential to emit fifty (50) T/yr or more of volatile organic compounds, or
- The facility is located in an ozone nonattainment area and, depending upon the classification of the nonattainment area, the facility has the potential to emit the following amounts of volatile organic compounds or oxides of nitrogen; provided that oxides of nitrogen shall not be included if the facility has been identified in accordance with 42 U.S.C. Section 7411a(f)(1) or (2) if the area is "marginal" or "moderate," one hundred (100) T/yr or more, if the area is "serious," fifty (50) T/yr or more, if the area is "severe," twenty-five (25) T/yr or more, and if the area is "extreme," ten (10) T/yr or more.
- The facility emits or has the potential to emit one hundred (100) T/yr or more of any regulated air pollutant. The fugitive emissions shall not be considered in determining whether the facility is major unless the facility is a "Designated Facility":

Uncontrolled HAP emissions were calculated by using the DEQ Automotive Coating EI spreadsheet (see the DEQ website) and setting paint use to 4.0 gallons per day (as limited by the permit). Then worst-case HAP emissions were determined for all paints listed in the spreadsheet. Then emissions were assumed to occur 2,080 hours per year as a worst-case assumption.

The following table compares the post-project facility-wide annual worst-case uncontrolled emission rate for all HAPs emitted by the source to the HAPS Major Source thresholds in order to determine if the facility is a HAPs Major Source.

HAP Pollutants	PTE (T/yr)	Major Source Threshold (T/yr)	Exceeds the Major Source Threshold?	
Ethyl benzene	0.61	10	No	
Methyl Isobutyl Ketone (MIBK)	1.25	10	No	
Naphthalene	2.32	10	No	
Toluene	1.90	10	No	
Styrene	2.49	10	No	
Xylene (o-, m-, p-isomers)	2.20	10	No	
Total	10.77	25	No	

#### Table 11 PTE FOR HAPs POLLUTANTS COMPARED TO THE HAPs MAJOR SOURCE THRESHOLDS

As presented in the preceding table the PTE for each HAP is less than 10 T/yr and the PTE for all HAPs combined is less than 25 T/yr. Therefore, this facility is not a HAPs Major Source subject to Tier I permitting requirements.

As discussed previously the Business Name facility is located in XXX County (AQCR 6X), which is designated as unclassifiable/attainment for  $PM_{2.5}$ ,  $PM_{10}$ ,  $SO_2$ ,  $NO_x$ , CO, and Ozone for federal and state criteria air pollutants. Therefore, the following table compares the post-project facility-wide annual PTE for all criteria pollutants emitted by the source to the applicable criteria pollutant Major Source thresholds in order to determine if the facility is a criteria pollutant Major Source.

0							
PTE (T/yr)	Major Source Threshold (T/yr)	Exceeds the Major Source Threshold?					
0.11	100	No					
0.11	100	No					
0.00	100	No					
0.20	100	No					
0.08	100	No					
12.21	100	No					
	(T/yr) 0.11 0.11 0.00 0.20 0.08	PTE (T/yr)         Threshold (T/yr)           0.11         100           0.11         100           0.00         100           0.20         100           0.08         100					

#### Table 12 PTE FOR CRITERIA POLLUTANTS COMPARED TO THE CRITERIA POLLUTANT MAJOR SOURCE THRESHOLDS

As presented in the preceding table the PTE for each criteria pollutant is less than 100 T/yr. Therefore, this facility is not a criteria pollutant Major Source subject to Tier I permitting requirements.

# PSD Classification (40 CFR 52.21)

40 CFR 52.21 Prevention of Significant Deterioration of Air Quality

The facility is not a major stationary source as defined in 40 CFR 52.21(b)(1), nor is it undergoing any physical change at a stationary source, not otherwise qualifying under paragraph 40 CFR 52.21(b)(1) as a major stationary source, that would constitute a major stationary source by itself as defined in 40 CFR 52. Therefore, in accordance with 40 CFR 52.21(a)(2), the PSD requirements do not apply.

# NSPS Applicability (40 CFR 60)

The facility is not subject to any NSPS requirements.

# **NESHAP Applicability (40 CFR 61)**

The facility is not subject to any NESHAP requirements in 40 CFR 61.

# MACT Applicability (40 CFR 63)

#### 40 CFR 63, Subpart HHHHHH National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources

§ 63.11169 What is the purpose of this subpart?

In accordance with §63.11169, subpart HHHHHH establishes national emission standards for hazardous air pollutants (HAP) for area sources involved in auto body refinishing operations that encompass motor vehicle and mobile equipment spray-applied surface coating operations.

§ 63.11170 Am I subject to this subpart?

In accordance with §63.11170(a), this automotive coating operation is subject to this subpart because the facility will be operated as an area source of HAP. The facility is a source of HAP that is not a major source of HAP, is not located at a major source, and is not part of a major source of HAP emissions. In addition, the facility will perform one or more activities listed in this section, including spray application of coatings, as defined in §63.11180, to motor vehicles and mobile equipment including operations that are located in stationary structures at fixed locations.

§ 63.11171 How do I know if my source is considered a new source or an existing source?

In accordance with §63.11171(b), the automotive coating operation is the collection of mixing rooms and equipment; spray booths, curing ovens, and associated equipment; spray guns and associated equipment; spray gun cleaning equipment; and equipment used for storage, handling, recovery, or recycling of cleaning solvent or waste paint. Paint stripping was not proposed as a business activity.

# {Use one of the following paragraphs as applicable: 1<sup>st</sup> paragraph for new facilities, 2<sup>nd</sup> paragraph for existing facilities.}

In accordance with §63.11171(c), this automotive coating operation is a new source because it will commence construction after September 17, 2007, by installing new paint stripping or surface coating equipment, and the new surface coating equipment will be used at a source that was not actively engaged in paint stripping and/or miscellaneous surface coating prior to September 17, 2007.

# {*or*}

In accordance with §63.11171(c), this automotive coating operation is an existing source because it commenced construction prior to September 17, 2007, by installing new paint stripping or surface coating equipment, and the new surface coating equipment will be used at a source that was actively engaged in paint stripping and/or miscellaneous surface coating prior to September 17, 2007.

§ 63.11172 When do I have to comply with this subpart?

# {Use one of the following paragraphs as applicable: $1^{st}$ paragraph for new facilities, $2^{nd}$ paragraph for existing facilities.}

In accordance with §63.11172(a)(2), because the initial startup of the facility will occur after January 9, 2008, the compliance date is the date of initial startup of the automotive coating operation.

# {*or*}

In accordance with §63.11172(a)(2), because the initial startup of the facility occurred prior to January 9, 2008, the compliance date is January 10, 2011.

§ 63.11173 What are my general requirements for complying with this subpart?

Because the facility has not proposed paint-stripping activities, the requirements of 63.11173(a) through (f) are not applicable. Because the facility is an automotive coating operation, in accordance with 63.11173(a), the permittee must meet the requirements of in paragraphs (e)(1) through (e)(5) of this section.

In accordance with 63.11173(f), each owner or operator of an affected automotive coating operation must ensure and certify that all new and existing personnel, including contract personnel, who spray apply surface coatings, as defined in 63.11180, are trained in the proper application of surface coatings as required by paragraph (e)(1) of this section. The training program must include, at a minimum, the items listed in paragraphs (f)(1) through (f)(3) of this section.

In accordance with §63.11173(g), as required by paragraph (e)(1) of this section, all new and existing personnel at an affected motor vehicle and mobile equipment or miscellaneous surface coating source, including contract personnel, who spray apply surface coatings, as defined in §63.11180, must be trained by the dates specified in paragraphs (g)(1) and (2) of this section. Employees who transfer within a company to a position as a painter are subject to the same requirements as a new hire.

Compliance with these requirements is assured by permit condition 17.

§ 63.11174

What parts of the General Provisions apply to me?

P-2010.0000 PROJ 00000

In accordance with §63.11174(a), Table 1 of this subpart shows which parts of the General Provisions in subpart A apply. Compliance with these requirements is assured by permit condition 16.

In accordance with §63.11174(b), an owner or operator of an area source subject to this subpart is exempt from the obligation to obtain a permit under 40 CFR part 70 or 71 provided that a permit under 40 CFR 70.3(a) or 71.3(a) is not required for a reason other than becoming area source subject to this subpart. This permit application and permitting action involve a Permit to Construct, and will not utilize the requirements and procedures in IDAPA 58.01.01.300-399 for the issuance of Tier I operating permits.

§ 63.11175 What notifications must I submit?

{Use one of the following paragraphs as applicable:  $1^{st}$  three paragraphs for new facilities,  $2^{nd}$  three paragraphs for existing facilities.}

In accordance with §63.11175(a), because the facility is a surface coating operation subject to this subpart, the initial notification required by §63.9(b) must be submitted. For this new operation, the Initial Notification must be submitted no later than 180 days after initial startup.

In accordance with §63.11175(b), because the facility is a new source, the permittee is not required to submit a separate notification of compliance status in addition to the initial notification specified in paragraph (a) of this subpart provided the permittee was able to certify compliance on the date of the initial notification, as part of the initial notification, and the permittee's compliance status has not since changed. The permittee must submit a Notification of Compliance Status on or before March 11, 2011. The permittee is required to submit the information specified in paragraphs (b)(1) through (4) of this section with the Notification of Compliance Status.

Compliance with these requirements is assured by permit condition 18.

## {*or*}

In accordance with §63.11175(a), because the facility is a surface coating operation subject to this subpart, the initial notification required by §63.9(b) must be submitted. For this existing operation, the Initial Notification must be submitted no later than on or before March 11, 2011.

In accordance with §63.11175(b), because the facility is an existing source, the permittee is not required to submit a separate notification of compliance status in addition to the initial notification specified in paragraph (a) of this subpart provided the permittee was able to certify compliance on the date of the initial notification, as part of the initial notification, and the permittee's compliance status has not since changed. The permittee must submit a Notification of Compliance Status on or before March 11, 2011. The permittee is required to submit the information specified in paragraphs (b)(1) through (4) of this section with the Notification of Compliance Status.

Compliance with these requirements is assured by permit condition 18.

§ 63.11176 What reports must I submit?

In accordance with §63.11176(a), because the permittee is an owner or operator of a paint stripping, motor vehicle or mobile equipment, or miscellaneous surface coating affected source, the permittee is required to submit a report in each calendar year in which information previously submitted in either the initial notification required by §63.11175(a), Notification of Compliance, or a previous annual notification of changes report submitted under this paragraph, has changed. Deviations from the relevant requirements in §63.11173(a) through (d) or §63.11173(e) through (g) on the date of the report will be deemed to be a change. The annual notification of changes report must be submitted prior to March 1 of each calendar year when reportable changes have occurred and must include the information specified in paragraphs (a)(1) through (2) of this section.

Compliance with these requirements is assured by permit condition 19.

Because the facility has not proposed to conduct paint stripping operations, the MeCl minimization plan requirements are not applicable (see permit condition 9).

§ 63.11177 What records must I keep?

In accordance with §63.11177, because the permittee is the owner or operator of a surface coating operation, the permittee must keep the records specified in paragraphs (a) through (d) and (g) of this section. Because the permittee has not proposed to conduct paint stripping operations, the requirements of paragraphs (e) and (f) of this section are not applicable. Compliance with these requirements is assured by permit condition 17.

§ 63.11178 In what form and for how long must I keep my records?

In accordance with 40 CFR 63.11178(a) because the permittee is the owner or operator of an affected source, the permittee must maintain copies of the records specified in §63.11177 for a period of at least five years after the date of each record. Copies of records must be kept on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date, and may be kept off-site after that two year period. Compliance with these requirements is assured by permit condition 17.

§ 63.11179 Who implements and enforces this subpart?

In accordance with §63.11179(a), this subpart can be implemented and enforced by the U.S. Environmental Protection Agency (EPA), or a delegated authority. At the time of this permitting action, the EPA has not delegated authority to the State of Idaho. However, IDAPA 58.01.01.107.03.i incorporates by reference all Federal Clean Air Act requirements including 40 CFR 63, Subpart HHHHHH. Therefore, the requirements of this subpart have been placed in the permit.

§ 63.11180 What definitions do I need to know?

Terms used in this subpart are defined in accordance with §63.11180.

# **Permit Conditions Review**

This section describes the permit conditions for this initial permit or only those permit conditions that have been added, revised, modified or deleted as a result of this permitting action.

Permit condition 1 establishes the permit to construct scope.

Permit condition 2 provides a description of the purpose of the permit and the regulated sources, the process, and the control devices used at the facility.

Permit condition 3 provides a process description of the facility.

Permit condition 4 provides a description of the control devices used at the facility.

Permit condition 5 establishes hourly and annual emissions limits for  $PM_{10}$  and VOC emissions from the automotive coating operation.

As mentioned previously, Permit Condition 6 establishes a 20% opacity limit for the paint booth stacks, vents, or functionally equivalent openings associated with the automotive coating operation.

As mentioned previously, Permit Condition 7 establishes that the permittee shall not allow, suffer, cause, or permit the emission of odorous gasses, liquids, or solids to the atmosphere in such quantities as to cause air pollution.

(If the booth is equipped with a heater. Note: If this condition is not place in the permit be sure to renumber the *Permit Condition references.*) Permit Condition 8 establishes that only natural gas or LPG is allowed to be used as fuel in the paint booth heater as proposed by the applicant.

Permit condition 9 establishes that the facility will not use MeCl to remove paint from vehicles at the facility. This was done because MeCl was not proposed to be used at this facility by the Applicant and the emissions were not included in the DEQ Automotive Coating EI Spreadsheet (see the DEQ website). In addition, Subpart HHHHHH has additional requirements for facilities that use MeCl to remove paint as mentioned previously in the discussion of Subpart HHHHHH in the MACT Applicability Section.

Permit condition 10 establishes a daily use limit for all coating materials used in the automotive coating process as proposed by the Applicant. This limit was established because it was the easiest way for the Applicant to demonstrate compliance with the  $PM_{10}$  and VOC emissions limit specified in permit condition 5 and the TAPs emissions limits specified in the DEQ Automotive Coating EI Spreadsheet (see the DEQ website).

Permit condition 11 establishes that the permittee conduct all automotive coating operations in the paint booth or preparation station with the filters in place, exhaust fan(s) operating, and door(s) or curtain(s) closed, that the operation shall use a HVLP spray gun, and that the permittee shall maintain and operate the paint booth and preparation station exhaust filter system in accordance with the manufacturer's specifications. This condition also defines what a booth and preparation station used for applying coating is.

Permit condition 12 establishes that the permittee shall maintain records of all odor complaints received, perform appropriate corrective actions, and maintain records of corrective actions taken at the facility for the automotive coating process. This was required because automotive operation operations are expected to have odors that might be offensive to their immediate neighbors.

Permit condition 13 establishes that the permittee shall maintain material purchase records and Material Safety Data Sheets (MSDS) for the automotive coating process. This condition was placed in the permit to ensure compliance with the Coating Materials Use Limit Permit Condition.

Permit condition 14 establishes that the permittee shall maintain daily usage records of pre-treatment wash primer, primer, topcoat, clear coat, and thinner/reducer materials used for the automotive coating process. This condition was placed in the permit to ensure compliance with the Coating Materials Use Limit permit condition.

Permit condition 15 establishes that the permittee shall maintain records as required by the General Provision recordkeeping requirements.

Permit condition 16 establishes parameters that will allow the facility to comply with the general operating requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 17 establishes parameters that will allow the facility to comply with the monitoring and recordkeeping requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 18 establishes parameters that will allow the facility to comply with the initial notification and reporting requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 19 establishes parameters that will allow the facility to comply with the annual notification and reporting requirements of 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Coating Operations unless the facility is exempt from HHHHHH.

Permit condition 20 establishes that the federal requirements of 40 CFR Part 63 are incorporated by reference into the requirements of this permit per current DEQ guidance.

# **PUBLIC REVIEW**

# **Public Comment Opportunity**

An opportunity for public comment period on the application was provided in accordance with IDAPA 58.01.01.209.01.c or IDAPA 58.01.01.404.01.c. During this time, there were/were no comments on the application and there was/was not a request for a public comment period on DEQ's proposed action. Refer to the chronology for public comment opportunity dates.

# **Public Comment Period**

A public comment period was made available to the public in accordance with IDAPA 58.01.01.209.01.c. During this time, comments were/were not submitted in response to DEQ's proposed action. Refer to the chronology for public comment period dates.

*(comments received)* A response to public comments document has been crafted by DEQ based on comments submitted during the public comment period. That document is part of the final permit package for this permitting action.

# **APPENDIX A – EMISSIONS INVENTORIES**

#### Coating Operation Emissions Calculations:

A daily coatings material use limit needs to be established for Automotive Coating operations that demonstrates compliance with State Law. Specifically, compliance with IDAPA 58.01.01.585 and .586 for toxic air pollutants (TAPs) needs to be determined. Therefore, DEQ staff created the DEQ Automotive Coating EI spreadsheet (see the DEQ website). This spreadsheet contains paints from two different manufacturers of paints used in the automotive coating industry and multiple paint systems for each brand. The paint brands chosen were based upon discussions with a national paint distributor with several stores throughout the state of Idaho. The TAPs data entered in the spreadsheet was taken from the MSDSs for the paints listed. Included in the calculations was a safety factor of 19% since all paints available were not analyzed. With this safety factor it is reasonably presumed that the data represents all available automotive coatings. The spreadsheet was then used to demonstrate that with 4.0 gallons per day of coating use, the ELs listed in IDAPA 58.01.01.585 and .586 would not be exceeded for any of the coatings listed in the spreadsheet. The 4.0 gallons per day of coating was then used to determine worst-case  $PM_{10}$  and VOC emissions from Automotive Coating operations (see the calculations as follows):

Table A.1 POST PROJECT HOURLY AND ANNUAL PM<sub>10</sub> POTENTIAL TO EMIT FOR THE AUTOMOTIVE COATING OPERATION

Coating Material	Daily Coating Use <sup>1</sup> (gal/day)	Annual Coating Use <sup>2</sup> (gal/yr)	Density <sup>3</sup> (lb/gal)	Paint Spray Gun TE <sup>4</sup> (%)	Booth Particulate Filters CE <sup>5</sup> (%)	Hourly PM <sub>10</sub> Emissions (lb-PM <sub>10</sub> /hr)	Annual PM <sub>10</sub> Emissions (T-PM <sub>10</sub> /yr)
Pre-treatment wash primer, primer, topcoat, clear, reducer, and hardener combined	4.0	1,460	16.71	65	98	0.02	0.09

<sup>1</sup> – Daily coating use was determined using the DEQ Automotive Coatings EI spreadsheet (see the DEQ website).

 $^{2}$  - Annual coating use is assumed to be daily coating use multiplied by 365 days per year.

<sup>3</sup> - The density of the paint was assumed to be the highest available using the DEQ Automotive Coatings EI spreadsheet (DEQ assumption for worst-case emissions).

<sup>4</sup> - The permit requires a minimum paint gun transfer efficiency of 65%. Therefore, PM<sub>10</sub> emissions are based up this minimum transfer efficiency.

 $^{5}$  - The permit requires a minimum PM<sub>10</sub> control efficiency of 98%. Therefore, PM<sub>10</sub> emissions are based up this minimum control efficiency.

# Table A.2 POST PROJECT HOURLY AND ANNUAL VOC POTENTIAL TO EMIT FOR THE AUTOMOTIVE COATING OPERATION

Coating Material	Daily Coating Use <sup>1</sup> (gal/day)	Annual Coating Use <sup>2</sup> (gal/yr)	VOC Content <sup>3</sup> (lb-VOC/gal)	Hourly VOC Emissions (lb-VOC/hr)	Annual VOC Emissions <sup>3</sup> (T-VOC/yr)
Pre-treatment wash primer, primer, topcoat, clear, reducer, and hardener combined	4.0	1,460	16.71	2.79	12.20

<sup>1</sup> – Daily coating use was determined using the DEQ Automotive Coatings EI spreadsheet (see the DEQ website).

 $^{2}$  - Annual coating use is assumed to be daily coating use multiplied by 365 days per year.

 $^{3}$  - The VOC content of the paint is assumed to be 100% VOC (DEQ assumption for worst-case emissions).

Uncontrolled emissions are based upon normal operation of the facility of 2,080 hrs/yr (8 hrs/day x 260 days/yr, normal business hours) with all coating operation occurring during this time. Since there is inherent prep time (the time spent preparing the automobile for the application of coating) and paint drying time (the time the automobile spends in the booth with the burner operating to facilitate hardening of the coating) this was considered to be the worst-case maximum for which emissions could occur.

Therefore, uncontrolled annual PM emissions are calculated using the annual PTE as calculated and backing out the 98% control efficiency of the filter system.

Uncontrolled annual PM<sub>10</sub> emissions from the coating operation are calculated as:

Uncontrolled Annual  $PM_{10}$  emissions =  $PM_{10}$  PTE (T- $PM_{10}$ /yr)  $\div$  (1 – Filter CE)

Uncontrolled Annual PM<sub>10</sub> emissions =  $0.09 \text{ T-PM}_{10}/\text{yr} \div (1 - 0.98) = 4.50 \text{ T-PM}_{10}/\text{yr}$ 

Therefore, uncontrolled annual VOC emissions are calculated using the annual PTE as calculated.

Uncontrolled annual VOC emissions are equal to annual PTE as calculated.

Uncontrolled Annual VOC emissions = VOC PTE (T-VOC/yr)

Uncontrolled Annual VOC emissions = 12.20 T-VOC/yr

[If a paint booth heater is used] Paint Booth Heater Emissions Calculations:

To determine worst-case emissions from the paint booth(s) heater(s) the maximum heat input rating of the burner was assumed to 2.0 MMBtu/hr with operation of 2,080 hrs/yr. {*Note: Use 2.0 MMBtu for natural gas burners and 1.2MMBtu/hr for LPG burners.*}

*(The following table is automated. Select the "Hourly Emissions" and "Annual Emissions" columns and press the F9 key. Note: The heat input is limited to 2.0 MMBtu/hr for worst-case maximum emissions.)* 

#### Table A.3 PAINT BOOTH HEATER POST PROJECT HOURLY AND ANNUAL POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS WHEN COMBUSTING NATURAL GAS

Emissions Unit	Rated Heat Input (MMBtu/hr) <sup>1</sup>	Annual Hours of Operation (hrs/yr)	Criteria Pollutant	Emissions Factors (lb/MMBtu) <sup>2</sup>	Hourly Emissions (lb/hr)	Annual Emissions (T/yr)
Paint Booth Heater 2.0			$PM_{10}$	0.0076	0.0152	0.016
			SO <sub>2</sub>	0.0006	0.0012	0.001
	2,080	NO <sub>X</sub>	0.094	0.188	0.196	
		CO	0.040	0.080	0.083	
			VOC	0.0055	0.011	0.011
			Pb	0.0000005	0.0000010	0.0000010

<sup>1</sup> - For worst-case emissions a maximum heat input of 2.0 MMBtu/hr was assumed.

<sup>2</sup> – Based on AP-42 Table 1.4-2 (7/98) for  $PM_{10}$ , SO<sub>2</sub>, VOC, and Pb and AP-42 Table 1.4-1 (7/98) for NO<sub>X</sub> and CO with a heat content of natural gas/LP of 1,000 Btu/scf.

As discussed previously uncontrolled emissions were based upon normal operation of the facility of 2,080 hrs/yr. Therefore, uncontrolled annual criteria pollutant emissions are calculated using the annual criteria pollutant PTE as calculated.

{Or use the following table if LPG is combusted. If the Applicant wants to use natural gas and LPG the tables must be combined and worst-case emissions must be used for each criteria pollutant. The following table is automated. Select the "Hourly Emissions" and "Annual Emissions" columns and press the F9 key. Note: The heat input is limited to 1.2 MMBtu/hr for worst-case maximum emissions.}

Table A.4 PAINT BOOTH HEATER POST PROJECT HOURLY AND ANNUAL POTENTIAL TO EMIT FOR CRITERIA POLLUTANTS WHEN COMBUSTING LIQUIFIED PETROLEUM GAS (LPG)

Emissions Unit	Rated Heat Input (MMBtu/hr) <sup>1</sup>	Annual Hours of Operation (hrs/yr)	Criteria Pollutant	Emissions Factors (lb/MMBtu) <sup>2</sup>	Hourly Emissions (lb/hr)	Annual Emissions (T/yr)
Paint Booth 1 Heater 1			$PM_{10}$	0.0087	0.0104	0.011
			SO <sub>2</sub>	0.0164	0.0197	0.020
	1.2	2,080	NOX	0.16	0.192	0.200
			CO	0.092	0.110	0.115
			VOC	0.012	0.014	0.015

<sup>1</sup> - For worst-case emissions a maximum heat input of 1.2 MMBtu/hr was assumed.

<sup>2</sup> – Based on AP-42 Table 1.5-1 (7/08) for PM<sub>10</sub>, SO<sub>2</sub> (see calculation as follows), NO<sub>X</sub>, CO, and VOC with a heat content of LPG of 1,000 Btu/scf.

LPG Combustion SO<sub>2</sub> Emission Factor Calculation:

```
Sulfur EF = 0.10 S lb/1,000 gal, with S in grain/100scf (AP-42, Table 1.5-1, 10/96)
Sulfur EF = 0.10 x (15 grain/100 scf) = 1.5 lb/1,000 gal Note: 15 grain/100 scf for LPG is a worst-case assumption for sulfur content of the fuel.
Sulfur EF = 1.5 lb/1,000 gal ÷ 0.0915 MMBtu/gal
Sulfur EF = 0.0164 lb-SO<sub>2</sub>/MMBtu
```

As discussed previously uncontrolled emissions were based upon normal operation of the facility of 2,080 hrs/yr. Therefore, uncontrolled annual criteria pollutant emissions are calculated using the annual criteria pollutant PTE as calculated.